

Technical Specifications:	
Weight Capacity	300 lbs.
Maximum Speed¹	Up to 4.0 mph in lowered position Up to 3.5 mph in elevated position
Ground Clearance²	2.42 in. at footplate 1.00 in. at motor bracket
Turning Radius²	22.5"
Overall Size^{2, 6}	Length: 43.23 in. with foot rigging Length: 38.6 in. without foot rigging Width: 23.4 in at the wheels Width: 25.5 in. with arm rests
Drive Controller	40A PG VR 2
Drive Wheels	10 in. flat free
Caster Wheels	6 in. flat free
Suspension	Active-Trac® with Mid-Wheel 6 Technology
Range^{1, 4}	Up to 15.29 miles w/ U1 batteries Up to 18.4 miles w/optional 40 Ah batteries
Component Weights⁵	Base: 225 lbs. w/ U1 batteries Base: 245 lbs. w/optional 40 Ah batteries Batteries: U1 - 24.5 lbs. Batteries: 40Ah - 32.2 lbs.
Drivetrain	Two motor, mid-wheel-6 drive
Brakes	“Intelligent Braking” electronic regenerative, disc park brake
Batteries³	(2) 12 volt, U-1 (2) Optional 40 Ah
Battery Charger	3.5 amp, off-board
Maximum Allowable Incline	6°
Maximum Angle Capacity	6°
Maximum Obstacle Climbing Ability	Lowered position 2.2 in. Elevated position 1.8 in.

Warranty	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors
<p>¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.</p> <p>² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.</p> <p>³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."</p> <p>⁴ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.</p> <p>⁵ Battery weight may vary based on manufacturer.</p> <p>⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.</p> <p><i>NOTE: This product conforms to all applicable ANSI/RESNA, ISO 7176 Series, and EN12184 standards. All specifications subject to change without notice.</i></p>	